

Stainless Steel Cylinders

Direct Unvented

25 Year Warranty

The following fittings are supplied with our Direct Cylinders:

- ✔ Inlet Control Set
- ✔ Temperature & Pressure Relief Valve
- ✔ 15mm / 22mm Tundish
- ✔ Expansion Vessel c/w Wall Mounting Bracket
- ✔ 2 x 3kW Immersion Heaters
- ✔ Installation & Maintenance Instructions
- ✔ Benchmark Logbook

Model No.	CAPACITY (Litres)	HEIGHT (mm)	DIAMETER (mm)	WEIGHT (Kg-EMPTY)	WEIGHT (Kg-FULL)	RATING
NDIR125L	120	933	550	25	149	B
NDIR150L	150	1120	550	30	185	C
NDIR180L	180	1308	550	33	218	C
NDIR210L	210	1496	550	37	253	C
NDIR250L	250	1746	550	40	296	C



Stainless Steel Cylinders

Indirect Unvented

25 Year Warranty

The following fittings are supplied with our Indirect Cylinders:

- ✓ Inlet Control Set
- ✓ Temperature & Pressure Relief Valve
- ✓ 15mm / 22mm Tundish
- ✓ Expansion Vessel c/w Wall Mounting Bracket
- ✓ 1 x 3kW Immersion Heater - On Cylinders 210L & Smaller
- ✓ 2 x 3kW Immersion Heaters - On Cylinders 250L & Greater
- ✓ Two Port Zone Valve
- ✓ Dual Thermostat
- ✓ Installation & Maintenance Instructions
- ✓ Benchmark Logbook

Model No.	CAPACITY (Litres)	HEIGHT (mm)	DIAMETER (mm)	WEIGHT (Kg-EMPTY)	WEIGHT (Kg-FULL)	RATING
NIND125L	120	933	550	25	149	B
NIND150L	150	1120	550	30	185	C
NIND180L	180	1308	550	33	218	C
NIND210L	210	1496	550	37	253	C
NIND250L	250	1746	550	40	296	C

Note: Slimline Direct & Indirect models available (478mm in Diameter)

