

SN SLi

Small vented water heaters



Small water heater SN SLi – cost-efficiency meets convenience | Different models for installation above single or multiple draw-off points. Any constant temperature can be selected from 35°C to 82°C or 85°C for hot water available at all times.

- › Open vented cylinders with 5–15 litre capacity (depending on model)
- › Low standby energy consumption
- › Heating output 2.0kW or 3.3kW (depending on model)
- › Active protection circuit for safety-first installation (high limit safety cut-out can be reset)
- › Profi-Rapid® for a quick installation

Model	SN 5 SL GB*	SN 10 SL GB*	SN 15 SL GB*
	221125	222192	222203
Rated capacity	l 5	10	15
Installation	Oversink	Oversink	Oversink
Rated output	kW 2.0	2.0	3.3
Fuse	A 10	10	16
Dimensions (H/W/D)	mm 421/263/230	503/295/275	601/316/295
Colour	white	white	white

Model	SNU 5 SL GB*	SNU 10 SL GB*
	221121	222198
Rated capacity	l 5	10
Installation	Undersink	Undersink
Rated output	kW 2.0	2.0
Fuse	A 10	10
Dimensions (H/W/D)	mm 421/263/230	503/295/275
Colour	white	white

*Frequency -50Hz | Phases - 1/N/PE | Rated Voltage - 230V

SHU SLi

Small unvented water heaters



Small water heater SHU SLi comfort – constant temperature at every turn | Ideal for reliably and continuously supplying several draw-off points with hot water at an infinitely variable constant temperature. A rotary selector makes temperature setting easy.

- › Cylinder with 5- or 10-litre capacity (depending on model)
- › 2.0 kW output
- › Active protection circuit for safety first installation (high limit safety cutout can be reset)
- › Maximum standby energy consumption 0.36 kWh
- › Profi-Rapid® for a quick installation
- › Available with SET A full unvented kit (227685) or with SET AX pressure relief valve (227688)
- › Larger wall mounted versions available in 30, 50, 100, and 150 litre capacities.

Model	SHU 5 SL GB Set A*	SHU 5 SL GB Set AX*
	227684	227687
Rated capacity	l 5	5
Installation	Undersink	Undersink
Rated output	kW 2.0	2.0
Dimensions (H/W/D)	mm 421/263/230	421/263/230
Colour	white	white

Model	SHU 10 SL GB Set A*	SHU 10 SL GB Set AX*
	227686	227689
Rated capacity	l 10	10
Installation	Undersink	Undersink
Rated output	kW 2.0	2.0
Dimensions (H/W/D)	mm 503/295/275	503/295/275
Colour	white	white

*Phases - 1/N/PE | Rated Voltage - 230V

SNU HOT + 3in1 cr tap

Instant piping hot water unit



Piping hot water system SNU HOT + 3in1 cr tap – hot water at a single turn | Piping hot water anytime for hot drinks and instant meals or cleaning purposes. The convenient push-and-turn tap and mixing levers remain cool to the touch for maximum safety. Fits under almost any sink.

- › Easy and fast installation thanks to low-pressure technology
- › 5-litre undersink water heater with 3in1 cr tap
- › 230 V power cable with earthed plug
- › Electronic controller for regulating water temperature to 97°C
- › Control electronics with automatic boil-dry prevention and safety temperature limiter

Model	SNU HOT + 3in1 cr tap
	232421
Rated capacity	l 5
Installation	Undersink
Rated Output	kW 2
Fuse	A 10
Dimensions (H/W/D)	mm 421/263/230
Colour	white

*Frequency -50Hz | Phases - 1/N/PE | Rated Voltage - 230V

STIEBEL ELTRON UK Ltd,
Unit 12 Stadium Court, Stadium Road,
Wirral International Business Park,
Bromborough, Wirral, CH62 3RP



STIEBEL ELTRON

Telephone: 0151 346 2300
Fax: 0151 334 2913
Email: sales@stiebel-eltron.co.uk
www.stiebel-eltron.co.uk

HOT WATER SMALL WATER HEATERS

Small water heaters.
Economy; and plenty of it!

- › Instantaneous water heaters
- › Vented water heaters
- › Unvented water heaters
- › Piping hot water heaters



DHE SLi

Electronically controlled instantaneous water heater



Fully electronically controlled instantaneous water heater DHE SLi – technology that keeps its promises | Annual operating cost reduction compared to hydraulic heaters. Hot water at precisely the temperature selected – for bathing, duty of care and leisure applications.

- › 18, 21, 24 kW (adjustable), 27 kW – 3Ph 415 V
- › 9.2–13.8 l/min (depending on model)
- › Exact required temperature to the precise degree
- › The economy monitor displays cost savings and CO₂ reductions
- › Electronic safety system with air detection
- › Bare-wire heating system with pressure-tested copper casing
- › ECO function to save water and energy
- › Profi-Rapid® for a quick installation
- › For multiple outlets of showers and wash hand basins

Model	DHE 18/21/24 SLi	DHE 27 SLi
	227493	227494
Rated voltage	V 415	415
Rated output	kW 18/21/24	27
Fuse	A 32/32/35	40
Max. permissible inlet temp	°C 65	65
DHW delivery	l/min 9.2/10.7/12.3	13.8
Dimensions (H/W/D)	mm 478/225/105	478/225/105
Weight	kg 4.5	4.5
Colour	white	white
IP-Rating	IP25	IP25

DHC-E | DHC

Electronic instantaneous water heater.



Electronic instantaneous water heater DHC-E and DHC – well tempered showering pleasure | Individually adjustable output to suit existing electrical systems and a precision electronic control unit to maintain the selected temperature. Short pipe runs ensure water and energy savings.

- › Saves up to 20% of energy compared to cylinder systems (DHC-E)
- › Anti-scalding protection (DHC-E)
- › Constant output for its entire service life (DHC-E)
- › Temperature selection in °F or °C (86°F to 125°F/30°C to 60°C) (DHC-E)
- › Oversink or undersink installation
- › Low energy consumption – no standby losses

Model	DHC-E 8/10	DHC-E 12
	224201	230628
Rated output	kW 7.2 9.6	12
Rated voltage	V 240	230
Phases	1/N/PE	1/N/PE
Frequency	Hz 50	50
Dimensions (H/W/D)	mm 360/200/110	360/200/110
Colour	white	white

Model	DHC 8
	073481
Rated output	kW 8.8
Rated voltage	V 230
Phases	1/N/PE
Frequency	Hz 50
Dimensions (H/W/D)	mm 360/200/104
Colour	white

DEM

Mini instantaneous water heater



Mini instantaneous water heaters DEM – ideal for wash hand basins | Perfect wherever small amounts of water at hand temperature are needed often. Electronically controlled set temperature without long supply lines or water and energy losses from manual adjustment.

- › For a single draw-off point
- › 3.5 kW, 4.4 kW, 5.7 kW and 6.5 kW (depending on model)
- › Effective bare-wire heating system
- › DEM for oversink and undersink installation

Model	DEM 3	DEM 4
	231001	231002
Rated output	kW 3.5	4.4
Rated voltage	V 230	230
Phases	1/N/PE	1/N/PE
Frequency	Hz 50	50
Dimensions (H/W/D)	mm 143/190/82	143/190/82
Colour	white	white

Model	DEM 6
	231215
Rated output	kW 5.7
Rated voltage	V 230
Phases	1/N/PE
Frequency	Hz 50
Dimensions (H/W/D)	mm 143/190/82
Colour	white

DN 3

Hand wash unit



Hand wash unit DN 3 – convenient hand-washing | Compact, hydraulically controlled instantaneous water heater for hand wash-basins. Easy water volume and temperature adjustment with an integrated rotary selector.

- › Ideal for hand washbasins
- › Easy to operate
- › Adjustable water volume and temperature
- › Integrated tap with stainless steel spout and water jet controller
- › Splash-proof to IP24

Model	DN 3
	231573
Rated output	kW 3.1
Rated voltage	V 230
Phases	1/N/PE
Frequency	Hz 50
Dimensions (H/W/D)	mm 143/190/82
Colour	white