



Induction Range 900mm wide

OE8017

- 4 x 5kW induction zones with 270mm diameter cooking area
- Automatic pan detection function cuts power when no pan is present, preventing harm to users, while saving energy
- 6mm thick high impact resistant glass ceramic surface will withstand hard knocks and is easy to clean
- Multiple internal cooling fans and overheat protection for long service life
- 4kW fan assisted oven





Induction Hob Features

- 4 x 5kW induction zones with 270mm diameter cooking area
- 6mm thick high impact glass ceramic surface
- Multiple internal cooling fans
- Overheat protection
- Automatic pan detection switches cooking zone off when pan removed
- Heating ON indication
- No pan-present indication
- Error mode indication
- Long life induction system 30,000 hours per zone
- · Easy to change air filters

Oven Features

- 4kW heating element
- Precise thermostatic control from 50 °C to 250 °C
- Fan assisted oven
- Power ON indicator light (green)
- Oven has reached desired temperature indicator light (amber)
- 180° side hinged doors
- Oven capacity 2 x GN1/1
- Heavy-duty easy remove wire chrome rack supports
- 4 position racking with anti tilt guards and safety stops

Cleaning and Servicing

- 6mm thick ceramic glass cooking surface, easy clean, spillages can just be wiped away
- · Easy clean stainless steel external finish
- Sits flush to the wall, reducing dirt ingress over the back
- Heavy-duty easy remove wire chrome rack supports
- · Stainless steel oven lining with removable base liner
- Access to most parts from the front and top of unit
- Easy change generator air filter

Overall Construction

- Permanent laser etched markings on fascia and knobs
- Fully framed 1.2mm steel chassis
- 1.2 mm stainless steel base panel
- 0.8 mm stainless steel side panels
- · Castors as standard
- Sits flush to the wall, recess for service

Induction Hob Construction

• 1.2 mm stainless steel welded bull nose and hob surround

Oven Construction

- 0.8 mm stainless steel outer door skin
- Reinforced door seal
- · Double insulated doors and side panels
- Stainless steel oven liner

Inclusive Accessories

2 chrome plated shelves

Available Options

- Adjustable legs
- Reduced power options available on request

Available Accessories


FI41 Filter kit






Technical Data

| | OE8017 |
|--|-------------------------------------|
| Width (mm) | 900 |
| Depth (mm) | 800 |
| Overall height (mm) | 900 |
| Hob height (mm) | 900 |
| Usable oven capacity h x w x d (mm) | 419 x 480 x 510 |
| Oven shelf size w x d (mm) | 480 x 510 |
| Hob | 4 zones |
| Fan | Single fan |
| Hob rating per induction zone (kW) | 5.0 |
| Oven rating (kW) | 4.0 |
| Total electrical power rating (kW) | 24 |
| Electrical supply 3N~+E 400V 50-60Hz Current Rating (Amps) | L1 = 34.8 L2 = 34.8 L3 = 34.8 |
| Net weight (kg) | 136.8 |
| Packed weight (kg) | 194 |
| Shipping volume (m3) | 1.2 |
| IPX Protection | IPX4 |










United Kingdom.



TEL: 01522 875555



WK Sales e-mail: sales@lincat.co.uk

■ International Sales Tel: +44 1522 503250
■ International Sales e-mail: export@lincat.co.uk



