


Opus 800

a natural evolution



Electric Griddles 600mm and 900mm wide

OE8205, OE8205/C, OE8205/R, OE8206, OE8206/C, OE8206/R

- Maximised cooking area, griddle plates sit flush to the sides of the unit
- Left and right independently controlled heat zones for flexibility and economy during quiet periods
- Precise thermostatic control up to 300°C for consistent results and economical operation
- Half ribbed plate and chrome plate options



OE8205



OE8206

Griddle Features

- Sheathed heating element
- 15mm thick griddle plate
- Maximised cooking area, griddle plates sit flush to the sides of the unit
- Welded splashguard for easy cleaning
- Left and right independently controlled heat zones
- Accurate thermostatic control up to 300°C
- 48mm round aperture grease drain
- Large 2 litre collection drawer

/R Half-ribbed plate option

- For attractive branding presentation marks

/C chrome plate option

- Easy to clean and for reduced heat radiation for a comfortable working environment and reduced energy costs
- Over temperature safety cut out
- Easy access reset button

Cleaning and Servicing

- Easy clean stainless steel external finish
- Welded splashguard for easy cleaning
- Easy clean 48mm round aperture grease drain
- Access to all parts from the front and top of unit

Overall construction

- Permanent laser etched markings on fascia and knobs
- 15mm thick griddle plate
- Top welded sealed plate
- 1.2 mm stainless steel welded bull nose and surround
- 1.2 mm stainless steel base panel
- 1.2 mm stainless steel side panels
- Welded stainless steel debris collection drawer
- Supplied on height adjustable 55-70mm legs
- Sits flush to the wall, recess for services

Inclusive Accessories

- Scraper (not for chrome models)

Available Options

- /R Half-ribbed plate
- /C Chrome plate

Available Accessories

- OA8972 Pedestal with doors for units 600mm wide
- OA8917 Floor stand for units 600mm wide
- OA8973 Pedestal with doors for units 900mm wide
- OA8914 Floor stand for units 900mm wide
- LK11 long leg kit

Technical Data

	OE8205	OE8206
With chrome plate	OE8205/C	OE8206/C
With half-ribbed plate	OE8205/R	OE8206/R
Width (mm)	600	900
Depth (mm)	800	800
Overall height (mm)	430	430
Height to hob (mm)	300	300
Cooking area w x d (mm)	590 x 500	890 x 500
Number of individually controlled heat zones	2	2
Heat input per zone (kW)	4	6
Total electrical power rating (kW)	8	12
Electrical supply 1N~+E 230V 50-60Hz Current Rating (Amps)	34.8	52.2
Electrical supply 3N~+E 400V 50-60Hz Current Rating (Amps)	L1 = 17.4 L2 = 17.4	L1 = 17.4 L2 = 17.4 L3 = 17.4
Net weight (kg)	87	96
Packed weight (kg)	116	130
Shipping volume (m3)	0.6	0.8
IPX Rating	IPX4	IPX4

OE8205

OE8206

